



PRODUCT-DETAILS

3GBA282220-ADMIN

IE3 (BIS) Premium Efficiency Cast Iron Motors,
75 kW, 415 V (3GBA282220-ADMIN)



General Information

Product ID:	3GBA282220-ADMIN
ABB Type Designation:	M2BAX 280SMB 4
Catalog Description:	IE3 (BIS) Premium Efficiency Cast Iron Motors, 75 kW, 415 V (3GBA282220-ADMIN)
Display Name:	3GBA282220-ADMIN

Ordering

ABB Type Designation:	M2BAX 280SMB 4
Invoice Description:	M2BAX 280SMB 4
Product Name:	3-Phase squirrel cage motor
Product Type:	IBA3__M2BAX_IE3_CI
Country of Origin:	India
Customs Tariff Number:	85015290
Medium Description:	75kW, 4 Poles, Frame Size 280, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GBA282220-ADMIN)

Short Description: 75kW, 4P, Frame Size 280, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Conn	Temp Class	Network Freq	Network Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	400 V	75.00 kW	1485 r/min	133.00 A	0.860	95.00 %	483.00 N·m	7.70
D	--	50 Hz	415 V	75.00 kW	1485 r/min	133.00 A	0.830	95.00 %	482.00 N·m	7.70

Connection Configuration: D

Temperature Class Default: --

Input Voltage (U_{in}): 415 V

Frequency (f): 50 Hz

Output Power: 75 kW

Altitude: 1000 m

Ambient Temperature: 50 °C

IC Class: IC411

IE Class Data (50 Hz):
 IE Class IE3
 Full Load (100%) 95.0 %
 Partial Load (75%) 95.0 %
 Partial Load (50%) 94.0 %

IP Class: IP55

Insulation Class: ICLF

Direction of Rotation: Both sides

Number of Poles (High): 4

Two Speed Motor: No

Type of Duty: S1

Voltage Code: D

Mechanical

Frame Material: Cast Iron

Frame Size: 280

Bearing: 6316/C3

Bearing NDE: 6316/C3

IM Class: IMB3 IM1001

Terminator Box Location: D-End top

Dimensions

Product Net Depth / Length: 1052 mm

Product Net Height: 775 mm

Product Net Width:	572 mm
Product Net Weight:	573 kg
Gross Weight:	593 kg

External Classifications and Standards

UNSPSC:	26101100
----------------	----------

Categories

Products > Motors and Generators > IEC Low Voltage AC Motors > General Performance Motors > IE3 (BIS) Premium Efficiency Cast Iron Motors

